

## Capstone® 500 ANSI • CE • UKCA • CSA • Ballistic •

Fits over most prescription glasses // Soft vinyl goggle body conforms to facial contours // Goggle provides protection against dust and chemical splash // Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance // Passes EN166 3 & 4, liquid droplets and large dust // Some options passes Ballistic MIL-PRF-32432 High Velocity Impact standards

### Gray Body with Quick Release Strap | 3 Variations

- EGG504T     Clear **H2X AF**
- EGG504TIR3    3.0 IR Filter **H2X AF**
- EGG504TIR5    5.0 IR Filter **H2X AF**

**i** Fits over most prescription glasses.



### General Specifications

Weight: 92 gm  
 PD: 68 mm  
 Bridge: 45 mm  
 Lens base: 5.5 curve  
 Lens size diagonal: 154 mm  
 Lens size vertical: 78 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 91 mm  
 Overall width (hinge - hinge): 180 mm  
 Strap length: 540 mm

### Materials

Lens: polycarbonate  
 Body: polycarbonate & polyvinyl chloride (PVC)  
 Headband: textile elastic  
 Nosepiece: polyvinyl chloride (PVC)

Part No.	Lens Marking	Frame Marking
EGG504T	2C-1.2 P 1 BT N CE	P EN166 3 4 BT CE UKCA
EGG504TIR3	3 P BT N CE	P EN166 3 4 BT CE UKCA
EGG504TIR5	5 P BT N CE	P EN166 3 4 BT CE UKCA

### Lens Marking Symbols

Code - field of use  
 2 or 3: UV filter  
 5 or 6: Solar filter  
 Color perception  
 C: Unimpaired color perception  
 Protection class  
 1.2 - 6: Degree of visible light filtration  
 Optical class  
 1: High optical quality - no optical distortion  
 Mechanical Strength  
 B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s  
 T: Impact protection at extreme temperature conditions  
 Symbols  
 P: Manufacturer's mark  
 N: Filter with anti-fog  
 CE: Certification for European Union

### Frame Marking Symbols

Symbols  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear  
 3: Liquid droplets or splashes  
 4: Large dust particles  
 CE: Certification for European Union  
 UKCA: Certification for United Kingdom  
 Mechanical Strength  
 B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s  
 T: Impact protection at extreme temperature conditions