

Capstone 500


ANSI • CE • CSA • Ballistic •



Fits over most prescription glasses // Soft vinyl goggle body conforms to facial contours // Goggle provides protection against dust and chemical splash // Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical splash resistance // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Gray Body with Quick Release Strap | 2 Variations

-  GG 504T  Clear **H2X** AF
-  GG 504TM  Clear **H2MAX** AF

 Fits over most prescription glasses.



GG504TN

Part No.	Lens Markings	Frame Markings
GG504T	P Z87 + U6	P Z87 + D3 D4 / P c SEI Z94.3
GG504TM	P Z87 + U6 X	P Z87 + D3 D4 / P c SEI Z94.3

Lens Marking Symbols	Frame Marking Symbols
P: Manufacturer's mark	P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices	Z87: ANSI standard for eye and face protection devices
+: High impact	+: High impact
X: Tested anti-fog	D3: Droplet & Splash Test
UV Filter Transmittance	D4: Dust Test
U6: .01% max effective far UV • .1% max near UV	c SEI Z94.3: CAN/CSA standard for eye and face protection devices

General Specifications
Weight: 92 gm
PD: 68 mm
Bridge: 45 mm
Lens base: 5.5 curve
Lens size diagonal: 154 mm
Lens size vertical: 78 mm
Lens thickness: 2.3 mm
Strap length: 540 mm

Materials
Lens: polycarbonate
Body: polycarbonate & polyvinyl chloride
Headband: textile elastic
Nosepiece: polyvinyl chloride