


Capstone® 600 ANSI • CE • CSA • Ballistic •



Fits over most prescription glasses // Indirect ventilation system prevents fogging // Includes interchangeable cloth and neoprene straps // Co-material goggle provides superior protection against dust entry and chemical splash // Thermoplastic (TPE) body with universal nose bridge is flexible and contours to the user's face // Passes D3: Droplet and Splash Test // Passes D4: Dust Test // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

Gray Body with Adjustable Strap | 1 Variation

● G604T2 ● ● ● ● Clear H2XAF

i Fits over most prescription glasses.



Part No.	Lens Markings	Frame Markings	General Specifications	Materials
G604T2	P Z87 + U6	P Z87 + D3 D4 / P c SEI Z94.3	Weight: 84 gm PD: 68 mm Bridge: 45 mm Lens base: 6 curve Lens size diagonal: 167 mm Lens thickness: 2.3 mm Strap length: 540 mm	Lens: polycarbonate Body: polypropylene & thermoplastic elastomers Frame insert: thermoplastic vulcanizates Headband: polyester Nosepiece: thermoplastic elastomers Strap holder: nylon & styrene-butadiene rubber
Lens Marking Symbols P: Manufacturer's mark Z87: ANSI standard for eye and face protection devices +: High impact UV Filter Transmittance U6: .01% max effective far UV • .1% max near UV		Frame Marking Symbols P: Manufacturer's mark Z87: ANSI standard for eye and face protection devices +: High impact D3: Droplet & Splash Test D4: Dust Test c SEI Z94.3: CAN/CSA standard for eye and face protection devices		