

# DROP ZONE®

Four Interchangeable Lenses



**ANSI CE BALLISTIC**

Part No.	Black Temples
VGSB88KIT ●●●	AF Clear H2X
	AF Forest Gray H2X
	AF Orange H2X
	AF Vermilion H2X

Stylish contoured temples

Extremely lightweight

Rubber nosepiece

Easy to change replacement lenses

Passes MIL-PRF 32432 High Velocity Impact Standards

Drop Zone includes: removable temples, crush-resistant neoprene storage case, microfiber cleaning cloth, and four interchangeable lenses

## GENERAL SPECIFICATION





Bridge: 23.8mm
Closest Point Between Lens: 75mm
Closest Point Between Temple Tips: N/A
Lens Base: 7 Curve
Lens Size Diagonal: 134.4mm
Lens Size Vertical: 52.5mm
Lens Thickness: 2.2mm
Overall Length (Lens-Tip): 167mm
Overall Width (Hinge-Hinge): 135.5mm
Weight: 29.5gm
PD: 64mm

# DROP ZONE®

## PACKAGING

Sold individually in Venture Gear free standing clamshell  
 Case: 20 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	7 base wrap around lens
Parts	Polycarbonate	Special structure secured with the lens for easy interchange
Nose Piece	Polycarbonate & TPR	Soft nose pad slips on hard nose piece, universal fit
Temple	Polycarbonate	Co-injected soft temple tips for comfort
Temple Tips	TPR	
Hinge	Polycarbonate	3 barrel type
Screw	Stainless Steel	Standard hinge screw

LENS	LENS MARKING	FRAME MARKING
	Clear	P Z97 + U6
	Forest Gray	P Z97 + U6
	Orange	P Z87 + S
	Vermilion	P Z87 + S

## LENS MARKING

### Symbols:

P: Manufacturer's mark  
 Z87: ANSI standard for Eye and Face protection devices  
 +: High Impact  
 H: Small Head Size  
 S: Special Purpose

### UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%  
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%  
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%  
 U4: Max Effective Far UV= .04% / Max Near UV= .5%  
 U5: Max Effective Far UV= .02% / Max Near UV= .2%  
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

### Visible Light Filters:

L1.3: 85% Max. Visible Light  
 L1.7: 55% Max. Visible Light  
 L2.5: 29% Max. Visible Light  
 L3: 18% Max. Visible Light

## FRAME MARKING

### Symbols:

P: Manufacturer's mark  
 Z87: ANSI standard for Eye and Face protection devices  
 +: High Impact