

G201/G201T

PERFORATED GOGGLE



PART	LENS
EG201**	<input type="radio"/> Clear
EG201T**	<input type="radio"/> Clear (Anti-Fog)

- Perforated, provides excellent ventilation.
- Lenses provide 99.9% protection against harmful UV rays.



GENERAL SPECIFICATION
Bridge: N/A
Lens Base: Flat
Lens Size Diagonal: 144mm
Lens Size Vertical: 68mm
Lens Thickness: 2.0mm
Overall Length (Lens-Tip): N/A
Overall Width (Hinge-Hinge): 200mm
PD: 68mm
Weight: 79gm

G201/G201T

PERFORATED GOGGLE

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 144 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Lens inset in PVC frame
Frame	PVC	Polyvinyl Chloride
Nose Piece	PVC	Integral to frame
Elastic Band	60% polyester 40% rubber thread	

PART	LENS	LENS MARKING	FRAME MARKING
EG201	 Clear	2 - 1.2 P 1 F CE	CE P EN166 F
EG201T	 Clear (Anti-Fog)	2 - 1.2 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust