

Reatta® ANSI •



Adjustable rubber nosepiece // Straight back flexible temples // Vented lens allows airflow to prevent fogging // Custom imprinting available

Charcoal Frame | 2 Variations

- SCH4810DT • Clear **H2X AF**
- SCH4820D • Gray

Charcoal and Blue Frame | 3 Variations

- SNC4810D • Clear
- SNC4820D • Gray
- SNC4880D • I/O Mirror



Part No.	Lens Marking	Temple Marking
SCH4810DT	P Z87 + U6	P Z87 +
SCH4820D	P Z87 + U6 L2.5	P Z87 +
SNC4810D	P Z87 + U6	P Z87 +
SNC4820D	P Z87 + U6 L2.5	P Z87 +
SNC4880D	P Z87 + U6 L1.7	P Z87 +

General Specifications
Weight: 30 gm
PD: 68 mm
Bridge: 9.6 mm
Lens base: 9 curve
Lens size diagonal: 81.5 mm
Lens size vertical: 50 mm
Lens thickness: 2.3 mm
Overall width (hinge - hinge): 136 mm
Overall length (lens-tip): 165mm

Materials
Lens: polycarbonate
Frame: polycarbonate
Temples: polyvinyl chloride + polycarbonate
Hinge: polycarbonate
Screw: stainless steel
Nosepiece: polyvinyl chloride + polycarbonate

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact