



PYRAMEX
Perform At Your Peak

XSG® ANSI CE CSA



FOAM
PADDING



INCLUDES
STRAP

Flame resistant foam padding

Strap has quick fit retainer

Interchangeable temples and strap included

Part No.	Black Frame
EGB4010ST ●●●	AF Clear H2X
EGB4020ST ●●●	AF Gray H2X
EGB4080ST ●●●	AF I/O Mirror



XSG Kit ANSI CE BALLISTIC



FOAM
PADDING



INCLUDES
STRAP



MULTI
LENSES

Interchangeable lenses, temples, and strap

Black ballistic nylon case for storage

Passes MIL-PRF 32432 High Velocity
Impact Standards

Part No.	Black Frame
EGB4010KIT ●●●	AF Clear H2X
	AF Gray H2X
	AF Amber H2X



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●) or Ballistic (MIL-PRF-32432) (●) standards. For specific lens options visit our website or contact your sales representative.

XSG® and XSG Kit

General Specifications

Weight: 28 gm
 PD: 68 mm
 Bridge: 13.7 mm
 Lens base: 8.0 curve
 Lens size diagonal: 66.3 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Strap length: 420 mm
 Overall length (lens - tip): 163 mm
 Overall width (hinge - hinge): 136.5 mm
 Closest point between temples: 56 mm
 Closest point between lens: 18.5 mm

Materials

Lens: polycarbonate
 Foam: polycarbonate & ethylene vinyl acetate (EVA)
 Frame: nylon
 Temples: polycarbonate & polyvinyl chloride (PVC)
 Strap: polyester
 Screw: stainless steel
 Nosepiece: ethylene vinyl acetate (EVA)

Part No.	Lens Markings	Frame Markings
EGB4010ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
EGB4020ST	5 -2.5 P 1 F N CE	CE P EN166 F
EGB4080ST	5 -1.7 P 1 F CE	CE P EN166 F
EGB4010KIT	2 C - 1.2 P 1 F N CE 5 -2.5 P 1 F N CE 2 - 1.2 P 1 F N CE	CE P EN166 F CE P EN166 F CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact