

ZONE II®

Styled like a sports lens



Matte Black Frame

Part	Lens
ESB3310E ••	Clear
ESB3320E •••	Gray
ESB3345E ••	Ice Orange Mirror
ESB3375E ••	Blue Mirror

Red Wood Frame

Part	Lens
ESRW3320E ••	Gray
ESRW3370E ••	Silver Mirror

Silver Frame

Part	Lens
ESS3320E ••	Gray








- Lenses filter 99.9% of harmful UV rays.
- Straight back, rubber coated temple tips.
- Soft nose pad and temples provide a comfortable fit.
- Built-in nose pads elevate frame for precision fit and weightless wear.

GENERAL SPECIFICATION
Bridge: 9mm
Lens Base: 9.5 Curve
Lens Size Diagonal: 64mm
Lens Size Vertical: 43.5mm
Lens Thickness: 2.4mm
Overall Length (Lens-Tip): 160.5mm
Overall Width (Hinge-Hinge): 136.5mm
PD: 68mm
Weight: 32gm
Closest point between lens: 18.6mm
Closest point between temple tips: 87.0mm

PACKAGING

Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Full eye protection 9.5 curve lens
Frame	Nylon 6.6	Dual lens frame with side protection
Side Shield	N/A	N/A
Nose Piece	PVC	Universal, integral to frame
Temple	Polycarbonate	Spatula with soft tip end
Temple Tips	PVC	Slip on the temple
Hinge	Nylon/Polycarbonate	3 barrel type, integral to frame / temple
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB3310E	 Clear	2C - 1.2 P 1 F CE	CE P EN166 F
ESB3320E	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ESB3345E	 Ice Orange Mirror	2 - 3.1 P 1 F CE	CE P EN166 F
ESB3375E	 Blue Mirror	2 - 3.1 P 1 F CE	CE P EN166 F
ESS3320E	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ESRW3320E	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ESRW3370E	 Silver Mirror	2 - 3.1 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust